

N&C

Prestige Polished



Prestige Calacatta Polished

5 colours / 1 Finish / 4 Sizes

Prestige Polished

Prestige, an authentic force of nature, eternal in nobility and sophistication, is the true calling for modern Architecture.



Prestige Calacatta Polished & Prestige Emperador Black Polished

Prestige Polished

Prestige, an authentic force of nature, eternal in nobility and sophistication, is the true calling for modern Architecture.



Prestige Calacatta Polished

NCS188725 300x600x10.5mm
NCS188726 600x600x10.5mm
NCS188727 880x880x11mm
NCS188728 600x1200x11mm



Prestige Corinthian Beige Polished

NCS188729 300x600x10.5mm
NCS188730 600x600x10.5mm
NCS188731 880x880x11mm
NCS188732 600x1200x11mm



Prestige Travertino Grey Polished

NCS188733 300x600x10.5mm
NCS188734 600x600x10.5mm
NCS188735 880x880x11mm
NCS188736 600x1200x11mm



Prestige Fior Di Bosco Tortora
Polished

NCS188737 300x600x10.5mm
NCS188738 600x600x10.5mm
NCS188739 880x880x11mm
NCS188740 600x1200x11mm

Prestige Polished

Prestige, an authentic force of nature, eternal in nobility and sophistication, is the true calling for modern Architecture.



Prestige Emperador Black
Polished

NCS188725 300x600x10.5mm

NCS188726 600x600x10.5mm

NCS188727 880x880x11mm

NCS188728 600x1200x11mm



Prestige Polished

	Test Method	Test Result	N&C Value
Slip Resistance (Pendulum Test Values Rating)		-	
Water Absorption	EN ISO 10545-3	> 0.05% < 0.1%	
Breaking Strength	EN ISO 10545-4	≥ 1300 N	
Modulus of Rupture	EN ISO 10545-4	≥ 35 N/mm ²	
Resistance to Abrasion	EN ISO 10545-6	< 175mm ³	
Length	EN ISO 10545-2	According to the norm	
Width	EN ISO 10545-2	According to the norm	
Thickness	EN ISO 10545-2	According to the norm	
Straightness of Sides	EN ISO 10545-2	According to the norm	
Squareness	-	-	
Surface Flatness	EN ISO 10545-2	According to the norm	
Colour Resistance to Light Exposure	-	-	

Chemical Properties

	Test Method	Test Result	N&C Value
Resistance to Acids (weak)	EN ISO 10545-13	LA/LB	
Resistance to Acids (strong)	EN ISO 10545-13	LA/LB	
Resistance to House Hold Cleaning Products	EN ISO 10545-13	min UB	
Resistance to Staining	EN ISO 10545-14	4	