

N&C

Touch



Touch Light Grey

2 Colours / 2 Finishes / 3 Sizes

Touch

The urban chic appeal of cement shows its softer side with gentle colours and subtle texture.



Touch Light Grey & TouchWhite & Touch White Decor

Touch

The urban chic appeal of cement shows its softer side with gentle colours and subtle texture.



Touch White

NB15523 300x600x8.5mm
NB15520 270x420x7.7mm
NB15522 450x450x8.5mm



Touch Light Grey

NB15513 300x600x8.5mm
NB15510 270x420x7.7mm
NB15512 450x450x8.5mm



Touch White Decor

NB15524 300x600x8.5mm
NB15521 270x420x7.7mm



Touch Light Grey Decor

NB15514 300x600x8.5mm
NB15511 270x420x7.7mm



Touch

Technical Specifications Physical properties

	Test of Norm	Value of Norm	N&C Value
Slip Resistance (Pendulum Test Values Rating)	BS 7976-2:2002	BS 7976-2:2002	N/A
Water Absorption	EN ISO 10545 - 3	EN ISO 10545 - 3	< 17%
Breaking Strength	EN ISO 10545 - 4	EN ISO 10545 - 4	> 600N
Modulus of Rupture	EN ISO 10545 - 4	EN ISO 10545 - 4	>13N/mm ²
Resistance to Abrasion	EN ISO 10545 - 7	EN ISO 10545 - 7	N/A
Length	EN ISO 10545 - 2	EN ISO 10545 - 2	0.5%
Width	EN ISO 10545 - 2	EN ISO 10545 - 2	0.3%
Thickness	EN ISO 10545 - 2	EN ISO 10545 - 2	10%
Straightness of Sides	EN ISO 10545 - 2	EN ISO 10545 - 2	0.3%
Squareness	EN ISO 10545 - 2	EN ISO 10545 - 2	0.5%
Surface Flatness	EN ISO 10545 - 2	EN ISO 10545 - 2	-0.1% - -0.25%
Colour Resistance to Light Exposure			

Chemical Properties

	Test of Norm	Value of Norm	N&C Value
Resistance to Acids (weak)	EN ISO 10545 - 13	EN ISO 10545 - 13	Class LA
Resistance to Acids (strong)	EN ISO 10545 - 13	EN ISO 10545 - 13	Class LA
Resistance to House Hold Cleaning Products	EN ISO 10545 - 13	EN ISO 10545 - 13	Class A
Resistance to Staining	EN ISO 10545 - 14	EN ISO 10545 - 14	Class 5