

N&C

Time Polished



Time Snow Polished

9 colours / 1 Finish / 4 Sizes

Time Polished

Versatility is at the heart of this timeless collection. Time is constructed from rectified full bodied porcelain stoneware, boasting high technical characteristics and offered in a blend of warm and cool tones.



Time Snow Polished

Time Polished

Versatility is at the heart of this timeless collection. Time is constructed from rectified full bodied porcelain stoneware, boasting high technical characteristics and offered in a blend of warm and cool tones.



Time Snow Polished

NB18790 300x600x10mm
 NB18760 600x600x10mm
 NB18700 900x900x10.5mm
 NCS188524 600x1200x10.5mm



Time White Polished

NB18794 300x600x10mm
 NB18764 600x600x10mm
 NCS188527 600x1200x10.5mm



Time Cream Polished

NB18791 300x600x10mm
 NB18761 600x600x10mm
 NB18701 900x900x10.5mm
 NCS188531 600x1200x10.5mm



Time Beige Polished

NB18795 300x600x10mm
 NB18765 600x600x10mm
 NB18704 900x900x10.5mm

Time Polished

Versatility is at the heart of this timeless collection. Time is constructed from rectified full bodied porcelain stoneware, boasting high technical characteristics and offered in a blend of warm and cool tones.



Time Dove Polished
 NB18796 300x600x10mm
 NB18766 600x600x10mm



Time Silver Polished
 NB18792 300x600x10mm
 NB18762 600x600x10mm
 NB18702 900x900x10.5mm
 NCS188540 600x1200x10.5mm



Time Grey Polished
 NB18797 300x600x10mm
 NB18767 600x600x10mm
 NCS188543 600x1200x10.5mm



Time Carbon Polished
 NB18798 300x600x10mm
 NB18768 600x600x10mm
 NB18705 900x900x10.5mm

Time Polished

Versatility is at the heart of this timeless collection. Time is constructed from rectified full bodied porcelain stoneware, boasting high technical characteristics and offered in a blend of warm and cool tones.



Time Black Polished

NB18793 300x600x10mm

NB18763 600x600x10mm

NB18703 900x900x10.5mm

NCS188550 600x1200x10.5mm



Time

Technical Specifications Physical properties

	Test of Norm	Value of Norm	N&C Value
Slip Resistance (Pendulum Test Values Rating)	DIN51130 BS 7976	PTV36+(NR&AS) R10 NR&R11 AS	
Water Absorption	ISO10545-3 ISO	TIME20 0,03%	
Breaking Strength	10545-4 ISO	TIME20 BETWEEN 3200N & 6400N	
Modulus of Rupture	10545-4 ISO	TIME20 >50MM/M2	
Resistance to Abrasion	10545-6 ISO	TIME20 123MM3	
Length	10545-2 ISO	TIME20 +/-2%	
Width	10545-2 ISO	TIME20 +/-0,2%	
Thickness	10545-2 ISO	TIME20 +/-0,2%	
Straightness of Sides	10545-2 ISO	TIME20 +/-0,2%	
Squareness	10545-2 ISO	TIME20 +/-0,3%	
Surface Flatness	10545-2	TIME20 +/-0,2%	
Colour Resistance to Light Exposure			

Chemical Properties

	Test of Norm	Value of Norm	N&C Value
Resistance to Acids (weak)			
Resistance to Acids (strong)	CSTB3778	TIME20, 3 NO	
Resistance to House Hold Cleaning Products	CSTB3778	ALTERATION TIME20, 3 NO ALTERATION	
Resistance to Staining	ISO 10545-14	TIME20, 4-5 SIMPLE REMOVAL	